



Articlenumber: A0EP1P21V003
GTIN: 4050369081277
Weight incl. packaging 0,00 kg
Weight excl. packaging: 2,70 kg

Highlights

This active laser safety window kit with article number A0EP1P21003 offers an effective field of vision of 292 X 445 mm and consists as a sandwich structure of the laser safety window, the LaserSpy as a sensor and the required mounting material for the sensor. This active window is suitable for active protection against the High power Blue laser. Blue high-power lasers are gaining popularity due to their suitability for laser processing of gold, copper and bronze materials, e.g. in additive manufacturing, battery production and the manufacturing of power electronics.

COATING:	no coating
COLOUR:	gold
FILTER MATERIAL:	Plastic
FILTER TECHNOLOGY:	Absorption filter, Active protection
FILTER THICKNESS:	ca. 10mm
PROPERTIES:	Active laser protection, Protection from blue high-power lasers
PROTECTION CLASS / NORM:	EN 60825-4
VLT (APPROX.):	50%
VISUAL BRIGHTNESS:	Good
COLOUR RECOGNITION:	Good

DIN EN 60825-4

Test class T1

425-465 nm

d86min

1,9 mm

A86min

$2,83 \times 10^{-6} \text{ m}^2$

Protective Exposure limit (PEL)

$707 \times 10^6 \text{ W/m}^2$

Triggering time

max 40 ms

Test class T2

200-470 nm

Protection duration

105 s

Protective Exposure limit (PEL)

$40,7 \text{ kW/m}^2$

Optical Density (OD)

200-470 OD 10+